

HS701 SELF LOADING VERSION

PETROL ENGINE

Brand.....HONDA
 Type.....GX270
 Pistons and displacement..... single-cylinder 270 cc
 Max gross power 8,4 HP - 6,3 kW @3600 rpm
 Starting..... manual
 Fuel tank.....5,3 liters
 Granted noise levelLwa 99 dB

Brand.....HONDA
 Type.....GX390
 Pistons and displacement..... single-cylinder 389cc
 Max gross power 11,7 HP - 8,7 kW @3600 rpm
 Starting..... electric
 Fuel tank.....6,1 liters
 Granted noise levelLwa 99 dB

DIESEL ENGINE

Brand.....KUBOTA
 Type.....OC 95
 Pistons and displacement..... single-cylinder 416cc
 Max gross power9,4 HP - 7 kW @3600 rpm
 Starting..... electric
 Fuel tank.....5,5 liters
 Granted noise level Lwa 101 dB

DISTRIBUTOR

Type.....mechanical

HYDRAULIC PUMPS

Number and type..... n° 3 gear pumps

TRACKS

Track tensioner.....grease
 Track width..... 180 mm
 Rollers per side..... 3
 Undercarriage width open/close..... 758- 1058 mm

PERFORMANCE

Translation speed
 ■ petrol engine GX270.....2,2 - 3,3 km/h
 ■ petrol engine GX390.....2,8 - 4 km/h
 ■ diesel engine 2,2 - 3,3 km/h
 Max. inclination 15°

CAPACITY700 kg

DUMPER BED CAPACITY

Rated volume (ISO 6483).....0,34 m³
 Struck volume.....0,28 m³

OPERATING WEIGHT (without operator)

Fixed/widening undercarriage-GX270 600 / 680 kg
 Fixed/widening undercarriage-GX390 640 / 720 kg
 Fixed/widening undercarriage-diesel engine. 655 / 735 kg

